



ISO 9001 Certified  
ISO 14001 Certified  
ISO 45001 Certified

Quality Management Systems  
Environmental Management Systems  
Occupational Health and Safety Management Systems

## ADVERTISED PLAN

### Stormwater Management Plan For Proposed Battery Project at Kiewa Valley Hwy, Baranduda VIC 3691.



**May 2024**

**Our Ref: 22219**

Level 1, 135 Fryers Street, Shepparton, Vic, 3630  
Telephone (03) 5820 7700 Facsimile (03) 5822 4878

Document Ref: 22219\_R\_SWMP\_rev3\_090524

**This copied document to be made available  
for the sole purpose of enabling  
its consideration and review as  
part of a planning process under the  
Planning and Environment Act 1987.  
The document must not be used for any  
purpose which may breach any  
copyright**

## TABLE OF CONTENTS

<b>1</b>	<b>INTRODUCTION.....</b>	<b>1</b>
<b>1.1</b>	<b>Background.....</b>	<b>1</b>
<b>1.2</b>	<b>Aim of the Report.....</b>	<b>1</b>
<b>2</b>	<b>EXISTING SITE DRAINAGE.....</b>	<b>2</b>
<b>2.1</b>	<b>Existing Site Conditions.....</b>	<b>2</b>
<b>2.2</b>	<b>Existing Stormwater Retention.....</b>	<b>2</b>
<b>3</b>	<b>PROPOSED DRAINAGE.....</b>	<b>3</b>
<b>3.1</b>	<b>Allowable Site Discharge .....</b>	<b>3</b>
<b>3.2</b>	<b>Runoff Coefficient.....</b>	<b>3</b>
<b>3.3</b>	<b>Stormwater Retention.....</b>	<b>3</b>
<b>3.4</b>	<b>Minor Flow System .....</b>	<b>4</b>
<b>3.5</b>	<b>Major Flow System .....</b>	<b>4</b>
<b>3.6</b>	<b>Neighbouring Property .....</b>	<b>4</b>
<b>4</b>	<b>CONCLUSION.....</b>	<b>4</b>
<b>5</b>	<b>APPENDICES.....</b>	<b>5</b>
<b>5.1</b>	<b>Appendix 1: Existing Conditions Plan.....</b>	<b>5</b>
<b>5.2</b>	<b>Appendix 2: Concept Drainage Plan.....</b>	<b>6</b>
<b>5.3</b>	<b>Appendix 3: Drainage Calculations .....</b>	<b>7</b>

**This copied document to be made available  
for the sole purpose of enabling  
its consideration and review as  
part of a planning process under the  
Planning and Environment Act 1987.  
The document must not be used for any  
purpose which may breach any  
copyright**

**ADVERTISED  
PLAN**

This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright

## 1 Introduction

### 1.1 Background

This report has been prepared on behalf of Birdwood Energy Pty Ltd to support the drainage conditions of a planning application for a proposed battery project in Kiewa Valley Highway, Baranduda.

The subject land is bounded by Kiewa Valley Highway to the West, Baranduda Drive to the South, Lot 1&2 of PS406394 to the East, middle creek to the North with an approximate area of 45.85 ha in total. The subject land is in the Industrial Zone (IN1Z), as per Wodonga Council.

A proposal has been made to use approximately 17 ha of the subject land as a battery energy storage facility as shown in Fig 1 and this report discusses the storm water management for the proposed project.




Figure 1- Aerial View of the Site

### 1.2 Aim of the Report

The purpose of this report is to provide a drainage strategy for the site, with consideration of the existing overland flow paths, stormwater retention, stormwater discharge, impact on neighbouring properties, and how the site is impacted in larger rainfall events.



## 2 Existing Site Drainage

### 2.1 Existing Site Conditions

The subject site is generally slopes in a north-eastern direction and mainly discharging into an open drain along the eastern boundary. It is understood that the overland flow from the site ultimately find its way to the Middle Creek. The site is largely undeveloped paddock and the property is currently vacant.



Figure 2- Existing Conditions Plan

### 2.2 Existing Stormwater Retention

The existing discharge from the site was calculated using Kinematic Wave equation as 708 litres/sec.

The existing onsite stormwater retention for the subject land has been calculated using the 100-year ARI retention spreadsheet for Baranduda with a runoff co-efficient of 0.2. The total stormwater retention storage required for the subject land is 2261m<sup>3</sup>. Refer Appendix 3 for detailed calculations.

There are two existing dams located outside the proposed development area. Currently the existing retention requirement is predominantly provided by these dams and the open drain along eastern boundary. The proposed development site drainage and retention will be contained within proposed development boundaries and wholly independent of the rest of the property.

**This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright**

### 3 Proposed Drainage

#### 3.1 Allowable Site Discharge

Allowable site discharge shall be limited to the pre-development runoff from the site which is calculated as 708 l/s. (See Appendix 3).

#### 3.2 Runoff Coefficient

The following runoff coefficients were used to derive an overall weighted coefficient for the post-development.

##### Battery Storage Footprint

Even though the battery storage containers will have impermeable roof areas, considering the allowance for stormwater runoff under the containers and permeable space between containers will allow water to infiltrate into the ground. Hence it can be assumed that the battery container area will have an overall runoff coefficient of 0.5.

Considering 0.9 coefficient for the proposed hardstand areas (laydown, access roads) and 0.5 for battery container areas, a common runoff coefficient for the proposed project footprint was estimated to be 0.75.

Accordingly, the overall post development runoff coefficient was calculated found to be 0.32 as per below table.

Location	Area (ha)	C Value
Proposed Project Footprint	9.52	0.75
Balance area	36.33	0.2
<b>Total</b>	<b>45.85</b>	<b>0.31</b>

**ADVERTISED  
PLAN**

#### 3.3 Stormwater Retention

The Stormwater retention requirement for the post development scenario was calculated using the volumetric runoff coefficient of 0.31 and the pre-development discharge rate of 708 l/s.

Using the 100-year ARI retention spreadsheet for Baranduda, the retention requirement was calculated as 4256m<sup>3</sup>. (See Appendix 3 for detailed calculations)

Effective retention requirement as part of the proposed works was calculated to be 1995 m<sup>3</sup> as per below table.

Pre-development Storage Requirement	2261 m <sup>3</sup>
Post Development Storage Requirement	4256 m <sup>3</sup>
<b>Effective storage requirement as per proposed development</b>	<b>1995 m<sup>3</sup></b>

### 3.4 Minor Flow System

Minor Drainage system consist of shallow v-drains to avoid nuisance water in the battery container areas and cut-off drain along the western end of the proposed development to redirect the upstream runoff away from the development. Existing open drain along eastern boundary is the main point of site discharge.

Runoff from more than 80% of the project footprint is captured into the proposed retention basin and the balance area will drain to the existing open drain.

The extent of the minor drainage work is shown on the concept drainage plan in Appendix 2.

### 3.5 Major Flow System

Since the overall lay of the land will not be altered by the proposed development, the major overland flow path will remain unchanged.

Indicative flow paths are shown in Figure 2.

The proposed retention basin is designed for the major flow system (100-year ARI).

### 3.6 Neighbouring Property

It is understood that in order to facilitate the battery project, a new extension is proposed in the neighbouring Wodonga Terminal Station (Ausnet). All drainage work associated with these proposed Ausnet works should be designed, approved and constructed in accordance with Ausnet drainage standards and Wodonga City Council's Infrastructure Design Manual guidelines. Portion of the connection infrastructure within the development may also be designed to Ausnet standards (where more onerous than other applicable regulations).

## 4 Conclusion

The existing site conditions such as overland flow path and site discharge will not be significantly affected by the proposed development. Proposed retention facility will overcompensate the possible effects of the proposed works and it will ensure that downstream and neighbouring properties will not be impacted.

**ADVERTISED  
PLAN**

## 5 Appendices

### 5.1 Appendix 1: Existing Conditions Plan

**This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright**

**ADVERTISED  
PLAN**



This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright

**ADVERTISED PLAN**

**Legend**

- Major Contour (Interval 1.0m)
- Minor Contour (Interval 0.20m)
- Fence Line
- Gate
- Edge of Concrete / Concrete Kerb
- Edge of Bitumen
- Centre Line of Bitumen
- Top of Bank
- Toe of Bank
- Edge of Water
- Overhead Electricity Line
- Temporary Bench Mark (TBM)
- Tree
- Dead Tree
- Sign
- Gate
- Fence Post
- Electricity Pole with Light
- Existing Surface Level
- Bitumen Area
- Dam

**Notes**

Every endeavour has been taken to locate visible services, however, there is no guarantee that all existing services are shown or located exactly on this plan. Positions and levels of these services should be proven on site before the commencement of any works.

Data is on MGA2020 Co-ordinate & Bearing datum based on GNSS observations to Baranduda PM 24 & TBM's on site. Data is on Ground Distances (not scaled).

Heights are to the Australian Height Datum (AHD) based on GNSS observations to Baranduda PM 24 (RL: 172.635).

For the purposes of plan clarity, some levels may not be displayed on this plan, however, they are visible in model space of this 'DWG'.


No responsibility is taken by Chris Smith & Associates, as to the location of underground services located in the survey. The client should investigate these matters to ensure they do not effect the possible development or project to be undertaken.

These notes are an integral part of the plan.


**CONDITIONS OF USE – PROVISION OF PLAN**

The provision of this plan is subject to the following conditions:

1. That this statement always remains with the plan as provided, even when it is passed onto a third party.
2. The plan is not altered in any way.
3. In the case of a plan of subdivision or consolidation, the plan provided is typically prepared in order to be certified by Council and approved by the Referral Authorities and is usually not a "registered plan" (not approved by Land Registry/Titles Office).
4. Chris Smith & Associates Pty. Ltd. accepts no responsibility whatsoever for any loss or damage suffered however to any person or corporation who may use or rely on the plan for any purpose.
5. Chris Smith & Associates Pty. Ltd. cannot accept any liability for any loss or damage however arising from future changes that may be applied to this plan. It is the responsibility of the recipient of this plan to ensure they have the most up to date version for their intended use.
6. Unless agreed in writing by our client, Chris Smith & Associates holds copyright and intellectual property rights over the product. However, our client may give written authority for "Third Parties" to use the plan for the purposes it was prepared.
7. Any use of the plan, or it's content, is on the basis that Chris Smith & Associates Pty. Ltd. is acknowledged as the author of the product and that due recognition is noted on any drawings or publications created or commissioned by the recipient of the plan.
8. That the following information is noted and accepted:
  - Where a coordinate system is used, the data may have been truncated and scaled/projected.
  - Where title boundary information is supplied, it is current as of the date of the file and is subject to variation, and should be read in conjunction with Land Registry titles and registered plans.
  - Chris Smith & Associates Pty. Ltd. accept no liability for any loss or damage however arising from future changes that may be applied to this data, or from the use of the data for purposes for which it was not intended.
  - Unless agreed in writing by our client, Chris Smith & Associates holds copyright over the product. However, our client may give written authority for the "third Parties" to use the data for the purposes it was prepared.
  - Chris Smith & Associates Pty. Ltd. is acknowledged as the author of the data.
9. Any further limitations of use that may be contained within the product itself must be accepted by the user.



REVISION	DATE	ZONE



Scale 1:1500 @ A1

**Chris Smith & ASSOCIATES**  
PTY LTD

CIVIL ENGINEERS · URBAN & REGIONAL PLANNERS · LAND SURVEYORS · PROJECT MANAGERS  
LEVEL 1 / 135 FRYERS STREET, SHEPPARTON, VIC. 3630  
PH: (03) 5820 7700 FAX: (03) 5822 4878 www.csmith.com.au

Designed Drawn Nick Dunham 17th March 2023  
Checked Nicholas Nightingale 27th March 2023  
Approved

**Birdwood Energy Pty Ltd.**  
**Battery Energy Storage System**  
Kiewa Valley Highway  
Baranduda, VIC 3691

**Plan of Existing Conditions**  
**as of the 16th March 2023**  
**Drawing No. 22219/01**  
Sheet No. 1 of 1

© Chris Smith & Associates ABN 14 627 882 064  
THIS DOCUMENT IS COPYRIGHT AND MAY ONLY BE USED FOR THE PURPOSE FOR WHICH IT WAS COMMISSIONED. UNAUTHORISED USE PROHIBITED. ALL DIMENSIONS AND LEVELS TO BE CHECKED ON THE PROJECT BEFORE COMMENCING ANY WORKS OR SHOP DRAWINGS. DRAWINGS NOT TO BE SCALED.

Rev. 0  
2221901r0.dwg




## 5.2 Appendix 2: Concept Drainage Plan

**This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright**


**ADVERTISED  
PLAN**






**LEGEND**


TITLE BODY	—
FENCE LINE	- - -
PROPOSED ROAD	==
STORMWATER DRAINAGE	—>
OPEN DRAIN	- - ->
RETENTION BASIN	■




TYPICAL CROSS SECTION - CUT-OFF DRAIN  
NOT TO SCALE



TYPICAL CROSS SECTION - MAIN ACCESS  
NOT TO SCALE




TYPICAL CROSS SECTION - INTERNAL ACCESS  
NOT TO SCALE



TYPICAL CROSS SECTION - RETENTION BASIN  
NOT TO SCALE

REVISION	DATE	ZONE
1 REVISED SITE LAYOUT	02-02-24	

**ADVERTISED PLAN**



Scale 1:1000 @ A1

**Chris Smith & ASSOCIATES**  
PTV LTD

CIVIL ENGINEERS  
URBAN & REGIONAL PLANNERS  
LEVEL 1 / 135 FRYERS STREET, SHEPPARTON, VIC. 3630  
PH: (03) 5820 7700 FAX: (03) 5822 4878 www.csmith.com.au

LAND SURVEYORS  
PROJECT MANAGERS

Designed: Sahan Dinesh  
Drawn: Tom Kerrins  
Checked: Tom Kerrins  
Approved: Tom Kerrins

Oct 2023  
Oct 2023

**Birdwood Energy Pty Ltd.**  
**Battery Energy Storage System**  
Kiewa Valley Highway  
Baranduda, VIC 3691

**Concept Drainage Plan**  
**Layout Plan**  
Drawing No. 22219-D01  
Sheet No. 1 of 1  
Rev. 1  
22219\_D01.dwg

© Chris Smith & Associates ABN 14 627 882 064  
THIS DOCUMENT IS COPYRIGHT AND MAY ONLY BE USED FOR THE PURPOSE FOR WHICH IT WAS COMMISSIONED. UNAUTHORISED USE PROHIBITED. ALL DIMENSIONS AND LEVELS TO BE CHECKED ON THE PROJECT BEFORE COMMENCING ANY WORKS OR SHOP DRAWINGS. DRAWINGS NOT TO BE SCALED.



### 5.3 Appendix 3: Drainage Calculations

**This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright**

**ADVERTISED  
PLAN**





**SUMMARY OF RETENTION CALCULATIONS (PRE-DEVELOPMENT)**

Client : **Birdwood Energy**  
Project : **Kiewa Valley Hwy, Baranduda**  
Ref. No. : **22219**

Temporal Rainfall Pattern data for A.R.I. >30 years.		
Catchment area.	45.85	ha
Volumetric runoff coefficient.	0.20	
Design A.R.I.	100	Years
Diameter of outfall discharge pipe.	300	mm
Hydraulic gradient of pipe.	1 in	
Pipe roughness coefficient 'k'.		mm
Discharge rate.	708.0	l/sec

**ADVERTISED  
PLAN**

Duration	30min		60min		120min		180min		360min		720min		1440min		*Adopted Cumulative Equivalent Intensity mm/hr	Cumulative		Excess m <sup>3</sup>								
	Intensity													Runoff		Outflow										
Interval min.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	CIA*(dt) /360 m <sup>3</sup>	708 l/s						
0																			0							
60				100	47.40	47.40		78.4	44.06	44.06	65.4	40.42	40.42	35.9	26.71	26.71	18.9	17.46	17.46	9.6	11.36	11.36	47.40	4346.58	2548.80	1797.78
120							21.6	12.14	56.20	22.9	14.15	54.57	27.5	20.46	47.17	28.6	26.43	43.89	22.8	26.98	38.34	56.20	5153.54	5097.60	55.94	
180										11.7	7.23	61.80	14.7	10.94	58.11	8.0	7.39	51.28	14.1	16.68	55.02	61.80	5667.06	7646.40	-1979.34	
240													10.8	8.04	66.14	8.9	8.22	59.51	6.9	8.16	63.18	66.14	6065.18	10195.20	-4130.02	
300													6.8	5.06	71.20	5.4	4.99	64.50	5.1	6.03	69.22	71.20	6529.11	12744.00	-6214.89	
360													4.3	3.20	74.40	8.2	7.58	72.07	4.1	4.85	74.07	74.40	6822.48	15292.80	-8470.32	
420																6.5	6.01	78.08	6.5	7.69	81.76	81.76	7497.31	17841.60	-10344.29	
480																4.4	4.07	82.14	4.4	5.21	86.97	86.97	7974.71	20390.40	-12415.69	
540																4.1	3.79	85.93	1.9	2.25	89.21	89.21	8180.86	22939.20	-14758.34	
600																2.7	2.49	88.43	3.4	4.02	93.24	93.24	8549.76	25488.00	-16938.24	
660																2.5	2.31	90.74	2.8	3.31	96.55	96.55	8853.55	28036.80	-19183.25	
720																1.8	1.66	92.40	2.1	2.48	99.03	99.03	9081.40	30585.60	-21504.20	
780																			2.5	2.96	101.99	101.99	9352.65	33134.40	-23781.75	
840																			3.8	4.50	106.49	106.49	9764.95	35683.20	-25918.25	
900																			1.5	1.77	108.26	108.26	9927.70	38232.00	-28304.30	
960																			1.7	2.01	110.27	110.27	10112.15	40780.80	-30668.65	
1020																			1.0	1.18	111.46	111.46	10220.65	43329.60	-33108.95	
1080																			0.8	0.95	112.40	112.40	10307.45	45878.40	-35570.95	
1140																			1.4	1.66	114.06	114.06	10459.35	48427.20	-37967.85	
1200																			1.1	1.30	115.36	115.36	10578.70	50976.00	-40397.30	
1260																			0.9	1.06	116.43	116.43	10676.34	53524.80	-42848.46	
1320																			0.7	0.83	117.26	117.26	10752.29	56073.60	-45321.31	
1380																			0.4	0.47	117.73	117.73	10795.69	58622.40	-47826.71	
1440																			0.5	0.59	118.32	118.32	10849.94	61171.20	-50321.26	

For 100 Year ARI

Maximum Retardation for no outflow condition =  
Maximum Retardation for given outflow =  
Outflow 300 mm dia. @ 1 in

10849.94 m<sup>3</sup>  
2260.64 m<sup>3</sup>

\* Used for plotting of Unit Area Envelope.

© Chris Smith & Associates Pty. Ltd. ABN: 14 627 882 064

THIS DOCUMENT IS COPYRIGHT & MAY ONLY BE USED FOR THE PURPOSE  
FOR WHICH IT WAS COMMISSIONED. UNAUTHORISED USE PROHIBITED.  
USED UNDER AGREEMENT WITH CHRIS SMITH & ASSOCIATES BY :-

- GREATER SHEPPARTON CITY COUNCIL.

**This copied document to be made available  
for the sole purpose of enabling  
its consideration and review as  
part of a planning process under the  
Planning and Environment Act 1987.  
The document must not be used for any  
purpose which may breach any  
copyright**

**SUMMARY OF RETENTION CALCULATIONS (POST-DEVELOPMENT)**

Client : **Birdwood Energy**  
Project : **Kiewa Valley Hwy, Baranduda**  
Ref. No. : **22219**

	Area	C
Proposed development	9.525 ha	0.75
Balance area	36.33 ha	0.2
Volumetric Coefficient	45.85	0.31

<b>Temporal Rainfall Pattern data for A.R.I. &gt;30 years.</b>		
Catchment area.	45.85	ha
Volumetric runoff coefficient.	0.31	
Design A.R.I.	100	Years
Diameter of outfall discharge pipe.	300	mm
Hydraulic gradient of pipe.	1 in	
Pipe roughness coefficient 'k'.		mm
Discharge rate.	708.0	l/sec

Duration	30min		60min		120min		180min		360min		720min		1440min		*Adopted Cumulative Equivalent Intensity mm/hr	Cumulative		Excess m <sup>3</sup>							
	Intensity													Runoff		Outflow									
Interval min.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	%	Equivalent Intensity mm/hr.	Cumulative Equivalent Intensity mm/hr.	CIA*(dt) /360 m <sup>3</sup>	708 l/s								
0																0									
60				100	47.40	47.40	78.4	44.06	44.06	65.4	40.42	40.42	35.9	26.71	26.71	18.9	17.46	17.46	9.6	11.36	11.36	47.40	6737.20	2548.80	4188.40
120							21.6	12.14	56.20	22.9	14.15	54.57	27.5	20.46	47.17	28.6	26.43	43.89	22.8	26.98	38.34	56.20	7987.99	5097.60	2890.39
180										11.7	7.23	61.80	14.7	10.94	58.11	8.0	7.39	51.28	14.1	16.68	55.02	61.80	8783.94	7646.40	1137.54
240													10.8	8.04	66.14	8.9	8.22	59.51	6.9	8.16	63.18	66.14	9401.04	10195.20	-794.16
300													6.8	5.06	71.20	5.4	4.99	64.50	5.1	6.03	69.22	71.20	10120.13	12744.00	-2623.87
360													4.3	3.20	74.40	8.2	7.58	72.07	4.1	4.85	74.07	74.40	10574.84	15292.80	-4717.96
420																6.5	6.01	78.08	6.5	7.69	81.76	81.76	11620.83	17841.60	-6220.77
480																4.4	4.07	82.14	4.4	5.21	86.97	86.97	12360.80	20390.40	-8029.60
540																4.1	3.79	85.93	1.9	2.25	89.21	89.21	12680.33	22939.20	-10258.87
600																2.7	2.49	88.43	3.4	4.02	93.24	93.24	13252.12	25488.00	-12235.88
660																2.5	2.31	90.74	2.8	3.31	96.55	96.55	13723.01	28036.80	-14313.79
720																1.8	1.66	92.40	2.1	2.48	99.03	99.03	14076.17	30585.60	-16509.43
780																			2.5	2.96	101.99	101.99	14496.61	33134.40	-18637.79
840																			3.8	4.50	106.49	106.49	15135.67	35683.20	-20547.53
900																			1.5	1.77	108.26	108.26	15387.93	38232.00	-22844.07
960																			1.7	2.01	110.27	110.27	15673.83	40780.80	-25106.97
1020																			1.0	1.18	111.46	111.46	15842.00	43329.60	-27487.60
1080																			0.8	0.95	112.40	112.40	15976.54	45878.40	-29901.86
1140																			1.4	1.66	114.06	114.06	16211.99	48427.20	-32215.21
1200																			1.1	1.30	115.36	115.36	16396.98	50976.00	-34579.02
1260																			0.9	1.06	116.43	116.43	16548.33	53524.80	-36976.47
1320																			0.7	0.83	117.26	117.26	16666.06	56073.60	-39407.54
1380																			0.4	0.47	117.73	117.73	16733.33	58622.40	-41889.07
1440																			0.5	0.59	118.32	118.32	16817.41	61171.20	-44353.79

For 100 Year ARI

Maximum Retardation for no outflow condition =  
Maximum Retardation for given outflow =  
Outflow 300 mm dia. @ 1 in

16817.41 m<sup>3</sup>  
4256.13 m<sup>3</sup>

\* Used for plotting of Unit Area Envelope.

© Chris Smith & Associates Pty. Ltd. ABN: 14 627 882 064

THIS DOCUMENT IS COPYRIGHT & MAY ONLY BE USED FOR THE PURPOSE FOR WHICH IT WAS COMMISSIONED. UNAUTHORISED USE PROHIBITED. USED UNDER AGREEMENT WITH CHRIS SMITH & ASSOCIATES BY :-  
- GREATER SHEPPARTON CITY COUNCIL.

This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright

**ADVERTISED PLAN**



Client : **Birdwood Energy Pty Ltd**  
 Project : **Kiewa Valley Hwy, Baranduda**  
 Ref. No. : **22219**

1% AEP Retention Requirement

**ADVERTISED  
PLAN**

Pre development	2261	m <sup>3</sup>
Post Development	4256	m <sup>3</sup>
Effective retention to be provided as part of the proposed works	1995	m <sup>3</sup>

**Retention Basin Capacity**

<u>Side A</u>		Excavated Depth	1.5 m
Top	110 m	Side Slope	1 in 4
Water Level	107.6 m	Freeboard	0.3 m
Base	98 m	Depth of Water	1.2 m
<u>Side B</u>			
Top	25 m		
Water Level	22.6 m		
Base	13 m		
		<b>CAPACITY</b>	<b>2224 m<sup>3</sup></b>
		<b>EXCAVATED VOLUME</b>	<b>3018 m<sup>3</sup></b>

**Allowable Discharge Rate ( Proposed Retention Basin)**

Total Site Area	45.85 ha
Pre-development discharge	708 l/s
Effective catchment of the retention basin	7.67 ha
Allowable discharge from retention basin	118 l/s

**This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any copyright**