








# Stormwater Management Plan

MLC  
10-14 Lofts Avenue  
Kew

**Presented to**  
Neoscape  
Sofiya Amira  
PROJECT MANAGER  
t: +61 447 084 433  
e: samira@neoscape.com.au  
w: www.neoscape.com.au

**Project Number**  
VIC230242



-  Structural
-  Geotechnical
-  Civil
-  Residential
-  Forensic
-  Building Services
-  Surveying

**Author**  
Nick Zaicos

Document Revision: B  
Template Version: v  
Template Name: WSUD

**Intrax Consulting Engineers Pty Ltd**  
ABN: 31 106 481 252  
**Head Office**  
Level 4, 469 La Trobe Street  
Melbourne, VIC 3000  
p: 03 8371 0100 f: 03 8371 0199  
w: www.intrax.com.au

## Table of Contents

<b>1</b>	<b>Executive Summary</b> .....	<b>3</b>
<b>2</b>	<b>Introduction</b> .....	<b>4</b>
<b>3</b>	<b>Planning Scheme Requirements</b> .....	<b>4</b>
<b>4</b>	<b>53.18-5 Stormwater Management Objectives Demonstration</b> .....	<b>6</b>
<b>5</b>	<b>53.18-6 Site Management Objectives</b> .....	<b>8</b>
	<b>Appendix A – MUSIC Report</b> .....	<b>10</b>
	<b>Appendix B – Stormwater Management Plan (Civil Engineering Drawings and Computations)</b> .....	<b>12</b>

### Copyright

©2024 Intrax Consulting Engineers Pty Ltd (ABN 31 106 481 252).

This document has been produced expressly for the client. The 'client' is defined as the person or persons named in this report/proposal or the purchaser of the services.

No part of this proposal including the whole of same shall be used for any other purpose nor by any third party without the prior written consent of Intrax Consulting Engineers Pty Ltd.

### Terms & Conditions

All documents are subject to the 'Intrax Terms and Conditions' and 'Intrax Terms and Conditions – NAC' documents. These documents are available on our website for your perusal.

This proposal is not intended for use by any other person or third party other than the named client.

### Document Revision History

Date	Rev	Author	Comments
20 August 2024	A	Nick Zaicos	First Issue
21 August 2024	B	Billy Browning-Briese	First Issue - Amendment

# 1 Executive Summary

This Stormwater Management Plan (SMP) provides an overview of the measures that will be incorporated within the development to ensure that best practice outcomes are achieved for the stormwater leaving the site, both in the buildings operation as well as during demolition and construction.

The requirements for the stormwater assessment for the development at 10-14 Lofts Avenue, Kew will comply with the planning scheme requirements as follows:

- Planning Scheme 53.18 Stormwater Management in Urban Development
  - 53.18-5 Stormwater management objectives for building and works
  - 53.18-6 Site management objectives

The key items that will be incorporated include:

- MUSIC modelling to demonstrate best practice water quality requirements, including:
  - Proprietary product - Atlan Filter (FIL.15-EMC) Half Height
- Sources of chemical pollutants located indoors and bundled if required
- Construction Management Plan to be prepared to ensure practices are implement throughout demolition and construction that minimise any pollutants entering the stormwater systems.

## 2 Introduction

This report provides an overview of the stormwater management strategy for the proposed residential development at 10-14 Lofts Avenue, Kew.

The objective of this report is to demonstrate that how stormwater management strategies have been incorporated into the design and how non-design commitments will be achieved.

The Stormwater Management Plan is based on the following documentation:

- Architectural Town Planning Drawings prepared by Architectus, dated 31.07.2024

The proposed development comprises of the following:

- Existing gates and fences to be removed
- Telstra Pit relocation to authority requirements
- Existing crossover to be demolished and extended
- Existing internal brick paving to be removed
- Existing lightweight buildings to be removed
- Tree removals per arborist assessment
- New 1500mm high fence and gates
- New internal gates
- Proposed shed
- Proposed new concrete hardstand / driveway
- Designated area for mulch bays

## 3 Planning Scheme Requirements

The water sensitive urban design requirements within the planning scheme are as follows:

- Boroondara Planning Scheme 53.18 Stormwater Management in Urban Development

### 3.1 Purpose

The purpose of clause 53.18 is:

*To ensure that stormwater in urban development, including retention and reuse, is managed to mitigate the impacts of stormwater on the environment, property and public safety, and to provide cooling, local habitat and amenity benefits.*

### 3.2 Requirements

The requirements for buildings and construction works applicable to this development are:

*An application to construct a building or construct or carry out works:*

- *Must meet all of the objectives of Clauses 53.18-5 and 53.18-6.*
- *Should meet all of the standards of Clauses 53.18-5 and 53.18-6.*

*An application must be accompanied by details of the proposed stormwater management system, including drainage works and retention, detention and discharges of stormwater to the drainage system.*

### 3.3 53.18-5 Stormwater management objectives for buildings and works

*To encourage stormwater management that maximises the retention and reuse of stormwater.*

*To encourage development that reduces the impact of stormwater on the drainage system and filters sediment and waste from stormwater prior to discharge from the site.*

*To encourage stormwater management that contributes to cooling, local habitat improvements and provision of attractive and enjoyable spaces.*

*To ensure that industrial and commercial chemical pollutants and other toxicants do not enter the stormwater system.*

#### **Standard W2**

The stormwater management system should be designed to:

- Meet the current best practice performance objectives for stormwater quality as contained in the Urban Stormwater - Best Practice Environmental Management Guidelines (Victorian Stormwater Committee, 1999).
- Minimise the impact of chemical pollutants and other toxicants including by, but not limited to, bunding and covering or roofing of storage, loading and work areas.
- Contribute to cooling, improving local habitat and providing attractive and enjoyable spaces.

### 3.4 53.18-6 Site Management Objectives

To protect drainage infrastructure and receiving waters from sedimentation and contamination.

*To protect the site and surrounding area from environmental degradation prior to and during construction of subdivision works.*

#### **Standard W3**

*An application should describe how the site will be managed prior to and during the construction period and may set out requirements for managing:*

- *Erosion and sediment.*
- *Stormwater.*
- *Litter, concrete and other construction wastes.*
- *Chemical contamination.*

### 3.5 Demonstration Objective Achieved

To demonstrate compliance with Planning Clauses 53.18-5 and 53.18-6 the following is provided:

- 53.18-5 Stormwater Management Objectives for Buildings and Works
  - MUSIC model to demonstrate best practice stormwater quality objectives through reductions in total suspended solids, phosphorus, nitrogen and gross pollutants. This demonstrates best practice performance objectives as per dot point 1 of Standard W2.
  - Assess locations that may contain chemical pollutants and provide measures to treat them within the proposed stormwater system.
  - Assess improvement of site pre to post development.
- 53.18-6 Site Management Objectives
  - Set requirements for a Construction Management Plan to ensure provisions through the demolition and construction of the project.

## 4 53.18-5 Stormwater Management Objectives Demonstration

### 4.1 Stormwater Management

It is assumed that the stormwater management objective for stormwater quality leaving the site is to be assessed against the proposed additions to the site only, which is additional hardstand and proposed shed. There are no changes proposed to the roof areas of the existing dwellings/structures to remain and it is therefore assumed the existing dwelling drainage requirements will remain and connect to the legal point of discharge via the proposed system .

It is noted that the proposed shed roof area is minimal, and therefore not considered appropriate for a rainwater tank for re-use.

The best practice performance objectives for stormwater quality leaving the site have been assessed through MUSIC modelling where a percentage reduction is deemed to achieve best-practice.

An analysis on the site has been conducted with the below best practice percentage reductions:

	Best Practice % Reduction	Achieved % Reduction
Total Suspended Solids (kg/yr)	80	83
Total Phosphorus (kg/yr)	45	72.1
Total Nitrogen (kg/yr)	45	57.5
Gross Pollutants (kg/yr)	70	100

Details of the assessment are contained within Appendix A, with the following key details:

- Inputs
  - Pavement Areas: 235sqm
  - Existing Roof Areas: 160sqm
  - Mulch Bay: 20sqm
  - Proposed Shed: 32sqm
- Stormwater management measures
  - Atlan Filter (FIL.15-EMC) Half Height (SQIDEP Verified)

An on-site stormwater detention system is also proposed to be provided to reduce post-development stormwater runoff to pre-development conditions. This is to be designed in accordance with council parameters as noted below:

Permissible Site Discharge (L/s)	5.7
On Site Detention Required (cub.m)	5.8

Refer Appendix B for proposed stormwater drainage design, including a typical stormwater detention system (subject to council approval). The on-site detention and treatment system arrangement is shown indicatively only for the purposes of discussion and is subject to change upon further design development and receipt of any planning conditions and council review and approval.

## 4.2 Chemical Pollutants

The likely sources of chemical pollutants and other toxic substances is assessed as:

- Mulch area
- Pollutants from vehicles access the site

The above areas are located externally and runoff into the stormwater system. The stormwater system has appropriate treatment components to address the above, refer Section 4.1.

## 4.3 Assessment of Pre and Post Development

The current use of the site is private residences.

The proposed development will provide facilities that support ongoing MLC/school operations. In turn, this results in improved education facilities for the community to enjoy.

## 5 53.18-6 Site Management Objectives

There are several pollutants that will be at risk of entering the stormwater system during the construction phase. It is important that these pollutants are addressed and planned for the risk to be mitigated prior to construction of the development to protect drainage infrastructure and receiving waters from sedimentation and contamination; and to protect the site and surrounding area from environmental degradation prior to and during construction of subdivision works.

For the construction phase, the performances objectives that will be adhered to are as per below:

- Suspended solids – effective treatment of 90% of daily run-off events.
- Litter – prevent all litter from entering the stormwater system. Such as construction packaging and paper.
- Other pollutants – limit the application, generation, and migration of the toxic substances to the maximum extent practicable.
  - Sediment – any exposed soils or stockpiles during earthworks.
  - Hydrocarbons – fuel or oil spills from construction equipment.
  - Toxic materials – preventing any cement slurry or solvents, cleaning agents from entering the system.

To reduce the load of pollutants entering the existing stormwater network, and associated waterways, a sediment management plan will be required. The plan may consider utilising silt fences, straw bales, gravel sausages and rumble grids (refer to Figures 4.1 – 4.3). The construction management plan will include site stormwater management objectives during the construction phase.




Figure 4.1. Silt fence installation (source: EPA Victoria 2004).



ing resources and tours




Figure 4.2. Straw bale and silt fence drop inlet filter combination (source: EPA Victoria 2004).





Figure 4.3. Gravel sausage layout for sediment (source: EPA Victoria 2004).

The details of how the above will be managed will be included as part of the Construction Management Plan for the project.

## Appendix A – MUSIC Report



## **Appendix B – Stormwater Management Plan (Civil Engineering Drawings and Computations)**




# MLC SCHOOL DEVELOPMENT

## 10-14 LOFTS AVENUE, KEW

### CIVIL SERVICES

SHEET No.	DOCUMENT TITLE
C0000	DRAWING INDEX
C0001	GENERAL NOTES
C0010	LEGEND OF SYMBOLS
C2000	SITE PLAN
C7000	SCHEDULES
C9000	DETAILS
C9001	DETAILS

B	CONCEPT	20.08.24	R.M
A	PRELIMINARY	02.08.24	R.M
Rev.	Remark/Comment	Date:	Appr.
Client: MLC			
Architect: NEOSCAPE PTY LIMITED			
 <small>www.intrax.com.au Intrax Consulting Group</small>			
Project: MLC SCHOOL DEVELOPMENT 10-14 LOFTS AVENUE, KEW			
Drawing: CIVIL SERVICES COVER SHEET			
THIS DRAWING HAS BEEN DOCUMENTED IN COLOR AND MUST BE PRINTED IN COLOR, OTHERWISE INFORMATION WILL BE LOST			
<b>CONCEPT</b> NOT FOR CONSTRUCTION			
Date:	JUL.2024	Engineer:	R.M
Scale @ A1:	NTS	Checked:	BBB
Reference No.	VIC240193	Drawing No.	C0000
		Drawn:	Y.X.C
		Sheets:	7
		Rev.	B

**GENERAL DRAINAGE NOTES**

- THE CONTRACTOR SHALL ADEQUATELY DRAIN THE SITE DURING ALL STAGES OF CONSTRUCTION.
- CONTRACTOR SHALL VERIFY ALL LEVELS DIMENSIONS AND SERVICES EXISTING AND REPORT ANY DISCREPANCIES TO BUILDER WITHIN 5 DAYS OF MOBILISATION TO SITE.
- ALL APPROPRIATE PERMITS SHALL BE OBTAINED AND FEES PAID FOR BY THE CONTRACTOR.
- ANY PAVEMENT OR FEATURES DAMAGED DURING THE COURSE OF THIS CONTRACT SHALL BE REINSTATED TO THEIR FORMER CONDITION.
- THE CONTRACTOR SHALL ARRANGE A SITE INSPECTION WITH THE CIVIL ENGINEERING SUPERVISING OFFICER PRIOR TO THE COMMENCEMENT OF WORK TO RECORD ANY DAMAGE TO EXISTING FEATURES.
- ALL EXISTING PIT COVERS, DOWNPIPE CONNECTIONS AND SIMILAR FEATURES IN CONSTRUCTION AREAS ARE TO BE ADJUSTED TO SUIT.
- ALL CONCRETE PAVEMENT SHALL BE FINISHED WITH A NON SKID FLOAT. (NO BROOMED FINISH).
- BEFORE COMMENCEMENT OF WORK A TEMPORARY BENCH MARK IS TO BE ESTABLISHED BY THE CONTRACTOR IN A POSITION ON SITE SAFE FROM DISTURBANCE.
- ANY SHORTFALL IN INDIGENOUS TOPSOIL REQUIRED TO BRING THE GARDEN AND GRASSED AREAS TO THE DESIGN LEVELS SHALL BE MADE UP WITH APPROVED IMPORTED TOPSOIL. NO ADDITIONAL PAYMENT WILL BE MADE FOR IMPORTED TOPSOIL.
- EXCAVATED MATERIAL SHALL BE STOCKPILED ON SITE AS DIRECTED BY THE SUPERINTENDENT. EXCESS TO BE REMOVED FROM SITE AT CONTRACTORS EXPENSE.
- TOPSOIL TO BE STRIPPED TO A DEPTH OF 150mm UNDER FILL AREAS AND ALL OTHER AREAS. THIS TOPSOIL SHALL BE STOCKPILED ON SITE AS DIRECTED BY SUPERINTENDENT. EXCESS SOIL SHALL BE REMOVED FROM THE SITE AT THE CONTRACTORS EXPENSE.
- ALL STORMWATER DRAINS SHALL BE BEDDED ON A MINIMUM OF 80mm COMPACTED THICKNESS 20 N.S. CLASS 3 FINE CRUSHED ROCK, IN SOIL BASED TRENCHES. INCREASE TO 200mm THICKNESS IN ROCK BASED TRENCHES.
- 100mm AND 150mm DIAMETER STORMWATER DRAINS SHALL BE LAID AT A MINIMUM GRADE OF 1:100, UNLESS OTHERWISE SHOWN.
- FOOTPATHS, DRIVEWAYS, ROADWAYS, KERBS, R.O.W.'S OR EXISTING FEATURES DISTURBED, BROKEN OR AFFECTED BY THE WORKS ARE TO BE REINSTATED TO THE COMPLETE SATISFACTION OF THE CITY ENGINEER OR HIS REPRESENTATIVE. ALL CONCRETE TO BE SAW CUT AND BROKEN OUT TO THE NEAREST JOINT.
- ALL NATURE STRIPS AND LAWN AREAS OUTSIDE PRIVATE PROPERTY TO BE REINSTATED WITH TOP SOIL AND SEEDED.
- CONTRACTOR TO CONTACT LOCAL COUNCIL ENGINEERING DEPARTMENT AT LEAST 48 HOURS PRIOR TO THE COMMENCEMENT OF CONSTRUCTION OF OUTFALL DRAINAGE TO ARRANGE FOR COUNCIL SUPERVISION AND INSPECTION IF REQUIRED BY COUNCIL.
- THE CONTRACTOR IS TO VERIFY ALL LOCATIONS AND DEPTH OF SERVICES WITH THE RELEVANT AUTHORITIES FOR THE CONSTRUCTION OF DRAINS AND SERVICES OUTSIDE THE PROPERTY BOUNDARY PRIOR TO THE COMMENCEMENT OF WORK. AND SHALL BE FULLY RESPONSIBLE FOR RECTIFICATION OF ANY DAMAGED SERVICE.
- ALL ADDITIONAL FILL MATERIAL REQUIRED DUE TO OVER EXCAVATION OR A SHORTFALL OF SUITABLE EXCAVATED MATERIAL SHALL BE IMPORTED AT THE CONTRACTORS EXPENSE.

MIN. REQUIREMENTS FOR EXPANSION AND ALLOWABLE IN FITTINGS		
SITE CLASS	MIN. REQUIRED EXPANSION JOINT CAPACITY	ALLOWABLE ROTATION
'E'	150mm	15°
'H'	70mm	15°
'P'	70mm PLUS ADDITIONAL REQUIREMENTS IN THE (MIN. DEPENDENT ON SITE CONDITION) CASE OF FILL	15°
'M'	MIN. 25mm LAGGING THROUGH FOOTINGS	NOT APPLICABLE

THE CONTRACTOR TO REFER SOIL CLASSIFICATION REPORT TO DETERMINE THE TYPE OF EXPANSION JOINT TO BE USED

**DRAINAGE NOTES:**

- ALL SURFACE DRAINAGE WORKS SHALL BE INSTALLED IN ACCORDANCE WITH CLAUSE 5.6.3 DRAINAGE REQUIREMENTS OF AS 2870-2011, WHEREIN FOR BUILDINGS ON MODERATELY, HIGHLY AND REACTIVE SITES:  
-SURFACE DRAINAGE SHALL BE CONTROLLED THROUGHOUT CONSTRUCTION AND BE COMPLETED BY THE FINISH OF CONSTRUCTION.  
-WHERE PIPES PASS UNDER THE FOOTING SYSTEMS, CLAY PLUGS ARE ADOPTED TO PREVENT THE INGRESS OF WATER.
- FOR BUILDINGS ON HIGHLY AND REACTIVE SITES, DRAINER SHALL PROVIDE DRAINAGE ARTICULATION TO ALL STORMWATER, SANITARY PLUMBING DRAINS AND DISCHARGE PIPES IN ACCORDANCE WITH CLAUSE 5.6.4 PLUMBING REQUIREMENTS, WHEREIN FLEXIBLE JOINTS IMMEDIATELY OUTSIDE BUILDING AND COMMENCING WITHIN 1m OF THE BUILDING PERIMETER ARE REQUIRED TO ACCOMMODATE THE REQUIRED DIFFERENTIAL MOVEMENT BASE ON THE SOIL CLASSIFICATION. REFER TABLE MIN. REQUIREMENTS FOR EXPANSION AND ALLOWABLE IN FITTINGS.
- DRAINAGE DESIGN IS IN ACCORDANCE WITH AS3500.

**MATERIALS**

- PROPOSED 1000 AND 1500 STORMWATER DRAINS AND FITTINGS SHALL BE UPVC CLASS SN8/10- UNLESS OTHER WISED SPECIFIED ON PLANS.
- PROPOSED 2250 AND 3000 STORMWATER DRAINS, USE UPVC CLASS SH TO AS1260, UNLESS OTHERWISE SPECIFIED ON THE PLANS.
- PROPOSED 3750 OR LARGER STORMWATER DRAINS, USE FRC RRJ JOINT CLASS 4 WHERE COVER EXCEEDS 600mm, UNLESS OTHERWISE SPECIFIED ON THE PLANS.
- PROPOSED 3750 OR LARGER STORMWATER DRAINS, USE RCP RRJ JOINT CLASS 2 WHERE COVER IS 600mm OR LESS, UNLESS OTHERWISE SPECIFIED ON THE PLANS.
- WHERE CONSTRUCTION LOADS CANT BE ACHIEVED, CONCRETE ENCASE THE PIPE OR IMPLEMENT LOW IMPACT CONSTRUCTION METHODS.
- IT IS THE CONTRACTORS RESPONSIBILITY TO CHECK PIPE TYPE AND CLASS REQUIREMENTS PRIOR TO CONSTRUCTION. IF THERE ARE ANY CONCERNS THEY SHOULD BE RAISED WITH THE DESIGNER PRIOR TO COMMENCEMENT OF CONSTRUCTION.

**SERVICE**

- WHERE PROPOSED SERVICES TRAVERSE EXISTING ASPHALT AND CONCRETE PAVEMENTS THE PAVEMENT IS TO BE SAW CUT TO FULL DEPTH OF PAVEMENT PRIOR TO EXCAVATION. THE INTERFACE BETWEEN EXISTING KERB AND CHANNEL (TO BE REMOVED) AND EXISTING ASPHALT SHALL BE SAWCUT.
- THE CONTRACTOR SHALL CO-ORDINATE THE LAYING OF ALL SERVICES TO AVOID CLASHES.
- LAY ALL SERVICES TO NOMINATED LEVELS WHERE GIVEN, OTHER SERVICES SHALL BE LAID TO COMPLY WITH MINIMUM COVER REQUIREMENTS.
- DIFFERENT PARALLEL SERVICES THAT ARE IN CLOSE PROXIMITY TO EACH OTHER MAY BE LAID IN A COMMON TRENCH, SUBJECT TO THE APPROVAL OF THE RELEVANT AUTHORITY AND THE SUPERINTENDENT.

**SITE DRAINAGE REQUIREMENTS - CONSTRUCTION STAGE:**


- PREVENT WATER PONDING AGAINST OR NEAR ANY EXISTING FOOTING.
- THE GROUND IN THE IMMEDIATE VICINITY OF THE PERIMETER FOOTING SHALL BE GRADED TO A FALL OF 50mm MIN. AWAY FROM THE FOOTING OVER A DISTANCE OF 1000mm (1:20) AND SHAPED TO PREVENT PONDING OF WATER (THIS INCLUDES THE GROUND UPHILL FROM THE FOOTING ON A CUT/FILL SITE) - WHERE FILLING IS PLACED ADJACENT TO THE BUILDING, THE FILLING SHALL BE COMPACTED AND GRADED TO ENSURE DRAINAGE OR WATER AWAY FROM THE BUILDING.
- ALL COLLECTED STORMWATER MUST BE DISCHARGED TO THE LPOD.
- INSTALL SUB-SURFACE DRAINAGE TO AS2439.1 100mm DIAMETER SN8 IN A 300mm WIDE TRENCH (MIN. FALL OF 1:100), BASE OF THE TRENCH IS FILLED WITH 12mm SINGLE SIZE AGGREGATE.  
-AG DRAINS MUST BE INSTALLED AT THE BASE OF ALL SITE CUTS THAT EXCEED 400mm IN HEIGHT, ALONG THE HIGH SIDE OF A SLOPING SITE AND POSSIBLY ALONG THE LOW SIDE OF A SLOPING SITE ALONG THE BOUNDARY. TO BE CONNECTED TO STORMWATER SYSTEM VIA A SILT PIT.  
-AG DRAINS TO BE LAID APPROX. 200mm INTO UNDISTURBED CLAY OR COMPACTED CLAY.
- TRENCHES MUST BE 'CLAY PLUGGED' OR CONCRETED WHEN PASSING PERPENDICULARLY UNDER ANY PART OF THE FOOTING AND ON ANY SLOTTED PIPE SIDE OF A CONNECTION PIT  
- ALL TRENCHES WITHIN 1500mm OF ANY FOOTING MUST BE EFFECTIVELY SEALED FROM SURFACE WATER, WITH AT LEAST THE TOP 300mm OF THE TRENCH FILLED WITH LOCAL CLAY COMPACTED TO AN IMPERMEABLE TOP LAYER. APPROVED MOISTURE BARRIER USE WITH TRENCHES IS AN OPTION.
- FLEXIBLE PLUMBING JOINTS ARE REQUIRED FOR H1/H2/E/P SITES TO ALLOW FOR EXPECTED VERTICAL GROUND MOVEMENTS (REFER GEOTECHNICAL REPORT). THE JOINTS MUST BE SET AT THE MIDWAY POINT WHEN INSTALLED & MUST ALSO INCORPORATE SWIVEL JOINTS IN THE SYSTEM  
- DRAINS EMERGING FROM UNDER THE FOOTING REQUIRE THE FLEXIBLE JOINT TO BE WITHIN 1000mm OF THE OUTSIDE OF THE PERIMETER FOOTING  
- INSTALLATION, LOCATION AND NUMBER OF JOINTS TO COMPLY WITH MANUFACTURER'S SPECS.

**EXISTING SERVICES**

- EXISTING SERVICES AND EQUIPMENT IS SHOWN IN BLACK AND/OR MARKED WITH 'EX'. CONFIRM LOCATION, DEPTH AND DETAILS OF ANY EXISTING SERVICES OR EQUIPMENT PRIOR TO COMMENCING WORKS AND ADVISE OF ANY DISCREPANCY. REFER EXAMPLE BELOW:

**GENERAL NOTES**

- THE BUILDER/CONTRACTOR SHALL PROVE ALL EXISTING SERVICES WITHIN 3 DAYS OF MOBILISATION OR ANY WORKS OCCURRING ON SITE.
- THESE PLANS ARE TO BE READ IN CONJUNCTION WITH THE ARCHITECTURAL & LANDSCAPE PLANS FOR EXTERNAL WORKS.
- ALL UNDERGROUND & SURFACE DRAINAGE WORKS SHALL BE INSTALLED IN ACCORDANCE WITH CLAUSE 5.6.3 DRAINAGE REQUIREMENTS OF AS 2870-2011 & AS3500.3-2018. SURFACE DRAINAGE SHALL BE CONTROLLED THROUGHOUT CONSTRUCTION AND BE COMPLETED BY THE FINISH OF CONSTRUCTION.
- ALL FINISHED SURFACE LEVEL TO BE SLOPED AWAY FROM FINISHED FLOOR LEVEL AND DRAIN TOWARDS STORMWATER PITS
- ALL INTERNAL DRAINAGE TO BE CONSTRUCTED AS PER AUSTRALIAN STANDARD AS3500.3-2018
- STORMWATER PIPE TO BE LAID 800mm CENTERS AWAY FROM EDGE OF SLAB UNLESS SPECIFIED OTHERWISE
- PROVIDE FLEXI JOINTS AND CLAY PLUGS AS PER AS2870
- BUILDER TO CONFIRM ALL PIT LEVELS AND COVERS PRIOR TO COMMENCEMENT OF CONSTRUCTION
- ALL DOWNPIPES LOCATION ARE PRELIMINARY ONLY. CONTRACTOR TO REFER LATEST ARCHITECT PLANS FOR EXACT LOCATION OF ALL DOWNPIPES. CONNECTION TO BE DONE ACCORDANCE TO PLUMBING STANDARD AS3500
- ALL CONCRETE JOINTS ARE SAWCUT JOINTS U.N.O. REFER TYPICAL DETAIL AND NOTES
- AUTHORITY APPROVAL REQUIRED PRIOR TO COMMENCEMENT OF CONSTRUCTION
- ALL HWS AND AC UNIT OVERFLOWS TO BE CONNECTED TO THE PROPOSED STORMWATER DRAINAGE SYSTEM
- AT NO TIME IS ANY EXISTING OR PROPOSED FOOTING TO BE UNDERMINED DURING CONSTRUCTION. BUILDER TO ENSURE AND CONFIRM PRIOR TO COMMENCEMENT OF CONSTRUCTION. THIS OFFICE TO BE CONTACTED IF ANY DISCREPANCY
- PROVIDE 2-N12 BARS \* 1200 LONG TOP FOR ALL RE-ENTRY CORNERS OF PITS. (TYPICAL).



B	CONCEPT	20.08.24	R.M
A	PRELIMINARY	02.08.24	R.M
Rev.	Remark/Comment	Date:	Appr.

Client:  
MLC

Architect:  
NEOSCAPE PTY LIMITED



Project:  
MLC SCHOOL DEVELOPMENT  
10-14 LOFTS AVENUE, KEW

Drawing:  
CIVIL SERVICES  
GENERAL NOTES

THIS DRAWING HAS BEEN DOCUMENTED IN COLOR AND MUST BE PRINTED IN COLOR, OTHERWISE INFORMATION WILL BE LOST

**CONCEPT**  
NOT FOR CONSTRUCTION

Date:	JUL.2024	Engineer:	R.M	Drawn:	Y.X.C
Scale @ A1:	NTS	Checked:	BBB	Sheets: 7	
Reference No.	VIC240193	Drawing No.	C0001	Rev.	B



© This drawing is copyright to Intrax Consulting Engineers. In part of this drawing shall be used for any other purpose without the prior written consent of Intrax Consulting Engineers.

# LEGEND OF SYMBOLS

## STORMWATER SERVICES

FOR PIPEWORK: DDDØ = PIPE DIAMETER IN MILLIMETERS  
 1.GG = PIPEWORK GRADE  
 ANY EXISTING PIPEWORK OR EQUIPMENT TO BE LOCATED PRIOR TO COMMENCING WORKS  
 ONSITE AND SIZE, DEPTH AND LOCATION TO BE CONFIRMED. ANY DIFFERENCES FROM THE  
 DESIGN TO BE REPORTED TO THE ENGINEER.

	EXISTING STORMWATER PIPE.
	INGROUND STORMWATER PIPE.
	SUSPENDED STORMWATER PIPE
	CHARGED STORMWATER PIPE. ENSURE PIPEWORK AND JOINTING METHOD SUITABLE FOR OPERATING PRESSURES. TEST TO ENSURE WATERTIGHT PRIOR TO CONCEALING
	AGI DRAIN
	NATURAL SWALE DRAIN REFER TO DETAIL PAGE
	STORMWATER RISING (PUMPED) MAIN. ENSURE PIPEWORK AND JOINTING METHOD SUITABLE FOR OPERATING PRESSURES. TEST TO ENSURE WATERTIGHT PRIOR TO CONCEALING
	EXISTING COUNCIL STORMWATER PIT.
	COUNCIL STORMWATER PIT - TO BE CONSTRUCTED IN ACCORDANCE WITH THE RELEVANT AUTHORITY STANDARDS. OBTAIN ALL REQUIRED PERMITS PRIOR TO CONSTRUCTION
	EXISTING INTERNAL GRATED PIT
	EXISTING INTERNAL JUNCTION PIT
	GRATED PIT
	GRATED PIT
	JUNCTION PIT
	BAFFLE PIT
	GRATED STORMWATER TRENCH. PIT/TRENCH NUMBER AA REFER PIT SCHEDULE FOR SIZE DEPTH AND COVER TYPE
	GRATED RISER TO MATCH FINISHED SURFACE LEVEL PROVIDE TRAFFICABLE CAP IN TRAFFICABLE AREAS
	INSPECTION OPENING TO MATCH FINISHED SURFACE LEVEL PROVIDE TRAFFICABLE CAP IN TRAFFICABLE AREAS
	DOWNPIPE DDDØ REFER ARCHITECTURAL PLANS FOR EXACT LOCATIONS AND SIZES
	STORMWATER PUMP. PUMP P-X REFER PUMP SCHEDULE FOR DETAILS
	RAINWATER TANK. RWT-X REFER DETAILS
	FLOOD GATE
	ONSITE DETENTION TANK-RECTANGULAR
	ONSITE DETENTION TANK-CIRCULAR
	TOP OF PIT

## PAVEMENTS

	PAVEMENT FINISHED LEVEL
	NEW CONCRETE KERB. TYPE BB REFER CONCRETE KERB LEGEND FOR DETAILS
	DOWEL PLATE JOINT. REFER DETAILS
	SAW CUT JOINT REFER DETAILS
	CONSTRUCTION JOINT REFER DETAILS
	PAVEMENT INVERT
	PAVEMENT RIDGE
	PAVEMENT SLOPE
	CONCRETE DRIVEWAY
	EXISTING CROSSOVER

## STRUCTURAL

	RETAINING WALL REFER STRUCTURAL DRAWINGS FOR DETAILS
	TOP OF RETAINING WALL
	BOTTOM OF RETAINING WALL
	FINISHED FLOOR LEVEL TO BE READ IN CONJUNCTION WITH ARCHITECTURAL PLANS
	CLAY PLUG
	FLEXI JOINT

## UTILITIES

	UTILITY ELECTRICITY ABOVE GROUND
	UTILITY ELECTRICITY BELOW GROUND
	UTILITY COMMS ABOVE GROUND
	UTILITY COMMS BELOW GROUND
	UTILITY SEWER MAIN
	UTILITY POTABLE WATER MAIN
	UTILITY NON-POTABLE WATER PIPEWORK
	UTILITY GAS MAIN
	UTILITY STORMWATER
	EXISTING UTILITY ELECTRICITY ABOVE GROUND
	EXISTING UTILITY ELECTRICITY BELOW GROUND
	EXISTING UTILITY COMMS ABOVE GROUND
	EXISTING UTILITY COMMS BELOW GROUND
	EXISTING UTILITY SEWER MAIN
	EXISTING UTILITY POTABLE WATER MAIN
	EXISTING UTILITY NON-POTABLE WATER MAIN
	EXISTING UTILITY GAS MAIN
	EXISTING UTILITY STORMWATER MAIN
	ELECTRICAL POWER POLE
	EXISTING ELECTRICAL POWER POLE
	ELECTRICAL PIT
	ELECTRICITY SUBSTATION
	COMMS PIT
	COMMS ROOM
	SEWER MANHOLE (NEW)
	EXISTING SEWER MANHOLE
	STREET FIRE HYDRANT

## MISC

	SITE BOUNDARY. SHOWN INDICATIVELY REFER SURVEY FOR INFORMATION
	EASEMENT REFER PLAN OF SUBDIVISION FOR INFORMATION
	SEDIMENT FENCE
	GROUND PLANE BOUNDARY
	PROJECT WORKS EXTENTS
	CONTOUR - MAJOR
	CONTOUR - MINOR
	DISCONNECTED SERVICE
	INSET BORDER
	OVERLAND FLOW ARROW

## IDENTIFIERS

	NOTE IDENTIFIER
	PIPE
	LONG SECTION
	SECTION
	TREE PROTECTION ZONE

B	CONCEPT	20.08.24	R.M
A	PRELIMINARY	02.08.24	R.M
Rev.	Remark/Comment	Date:	Appr.

Client:  
MLC

Architect:  
NEOSCAPE PTY LIMITED



www.intrax.com.au  
Intrax Consulting Group


Project:  
MLC SCHOOL DEVELOPMENT  
10-14 LOFTS AVENUE, KEW

Drawing:  
CIVIL SERVICES  
LEGEND OF SYMBOLS

THIS DRAWING HAS BEEN DOCUMENTED IN COLOR AND MUST BE  
PRINTED IN COLOR, OTHERWISE INFORMATION WILL BE LOST

<b>CONCEPT</b> NOT FOR CONSTRUCTION		
Date:	JUL.2024	Engineer: R.M
Scale @ A1:	NTS	Drawn: Y.X.C
Reference No.	VIC240193	Checked: BBB
Drawing No.	C0010	Sheets: 7
		Rev. B

© This drawing is copyright to Intrax Consulting Engineers. In part of this drawing shall be used for any other purpose without the prior written consent of Intrax Consulting Engineers.



LOFTS AVENUE

**SPECIFIC NOTES**

- 1 EXTEND EXISTING CROSSOVER TO THE STANDARDS AND SATISFACTION OF BOROONDARA CITY COUNCIL
- 2 CONNECT TO EXISTING PIT (EX1) TO THE SATISFACTION OF BOROONDARA COUNCIL. IL REQ. 42.10
- 3 ARCHITECT TO CONFIRM SHED DOWNPIPE CONNECTION LOCATION (TO BE CONNECTED TO ONSITE DETENTION SYSTEM).
- 4 ARCHITECT TO CONFIRM MULCH BAY FINISH.
- 5 ARCHITECT TO CONFIRM FINISHED FLOOR LEVEL OF SHED
- 6 PROVIDE ATLAN FILTER HALF-HEIGHT FIL-15-EMC-M OR APPROVED EQUIVALENT IN PIT IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS AND REQUIREMENTS
- 7 EXISTING DWELLING ROOF DRAINAGE TO CONNECT TO PROPOSED UNDERGROUND STORMWATER SYSTEM
- 8 ON SITE DETENTION AND WATER TREATMENT SHOWN INDICATIVELY ONLY. SUBJECT TO FURTHER DESIGN DEVELOPMENT.
- 9 PROVIDE KERB DOWNTURN/BATTER BETWEEN DRIVEWAY AND BOUNDARY AS REQUIRED

B	CONCEPT	20.08.24	R.M
A	PRELIMINARY	02.08.24	R.M
Rev.	Remark/Comment	Date:	Appr.

Client:  
MLC

Architect:  
NEOSCAPE PTY LIMITED




Project:  
MLC SCHOOL DEVELOPMENT  
10-14 LOFTS AVENUE, KEW

Drawing:  
CIVIL SERVICES  
SITE PLAN

THIS DRAWING HAS BEEN DOCUMENTED IN COLOR AND MUST BE PRINTED IN COLOR, OTHERWISE INFORMATION WILL BE LOST

**CONCEPT**  
NOT FOR CONSTRUCTION

Date:	JUL.2024	Engineer:	R.M	Drawn:	Y.X.C
Scale @ A1:	1:100	Checked:	BBB	Sheets:	7
Reference No.	VIC240193	Drawing No.	C2000	Rev.	B



© This drawing is copyright to Intrax Consulting Engineers. In part of this drawing shall not be used for any other purpose without the prior written consent of Intrax Consulting Engineers.



PIT SCHEDULE									
PITNO.	TYPE	INTERNAL DIMENSIONS LxW(mm)	SURFACE LEVEL	DEPTH (mm)	INLET PIPE DIA	INLET PIPE IL	OUTLET PIPE DIA	OUTLET PIPE IL	COVER TYPE DESCRIPTION
EX1	EXISTING	EXISTING	EXISTING	EXISTING	150	42.10	EXISTING	EXISTING - ASSUMED IL 42.08	EXISTING
01	JUNCTION PIT	600x600	42.90	780	150	42.14	150	42.12	CLASS C LID
02	JUNCTION PIT	1200x1200	43.44	1230	150	42.56	150	42.21	CLASS C LID. PROVIDE STEP IRONS
03	BAFFLE PIT	900x1900	43.41	840	450	42.61	150	42.57	CLASS C LID
04	GRADED PIT	900x900	43.56	930	450	42.65	450	42.63	CLASS C LID
05	GRADED PIT	900x900	43.63	960	450	42.69	450	42.67	CLASS C LID
06	GRADED PIT	900x900	43.87	1070	-	-	450	42.80	CLASS C LID. PROVIDE STEP IRONS

BUILDER TO CONFIRM ALL PIT LEVELS AND COVERS PRIOR TO COMMENCEMENT OF CONSTRUCTION

B	CONCEPT	20.08.24	R.M
A	PRELIMINARY	02.08.24	R.M
Rev.	Remark/Comment	Date:	Appr.

Client:  
MLC

Architect:  
NEOSCAPE PTY LIMITED




Project:  
MLC SCHOOL DEVELOPMENT  
10-14 LOFTS AVENUE, KEW

Drawing:  
CIVIL SERVICES  
SCHEDULES


THIS DRAWING HAS BEEN DOCUMENTED IN COLOR AND MUST BE PRINTED IN COLOR, OTHERWISE INFORMATION WILL BE LOST

**CONCEPT**  
NOT FOR CONSTRUCTION


Date:	JUL.2024	Engineer:	R.M	Drawn:	Y.X.C
Scale @ A1:	AS SHOWN	Checked:	BBB	Sheets:	7
Reference No.	VIC240193	Drawing No.	C7000	Rev.	B




**TRENCH CONDITIONS FOR DRAINAGE PIPE INSTALLATION (NOT UNDER PAVEMENTS)**  
NOT TO SCALE




**PIPE TRENCH UNDER PAVEMENT**  
NOT TO SCALE




**BARRIER KERB: TYPE B1**  
NOT TO SCALE




**TYPICAL PIPE PENETRATION DETAIL**  
SCALE 1:20




**TYPICAL DRIVEWAY PAVEMENT CROSS-SECTION**  
NOT TO SCALE




INDICATED ON PLAN  
**TYPICAL SAWCUT DETAIL (SCJ)**  
NOT TO SCALE



**ORIFICE PIT TYPICAL DETAIL**  
NOT TO SCALE



**PLAN VIEW**  
NOT TO SCALE



**SECTION A-A**  
NOT TO SCALE

B	CONCEPT	20.08.24	R.M
A	PRELIMINARY	02.08.24	R.M
Rev.	Remark/Comment	Date:	Appr.

Client:  
**MLC**

Architect:  
**NEOSCAPE PTY LIMITED**



Project:  
**MLC SCHOOL DEVELOPMENT  
10-14 LOFTS AVENUE, KEW**




Drawing:  
**CIVIL SERVICES  
DETAILS**

THIS DRAWING HAS BEEN DOCUMENTED IN COLOR AND MUST BE PRINTED IN COLOR, OTHERWISE INFORMATION WILL BE LOST

**CONCEPT**  
NOT FOR CONSTRUCTION

Date:	JUL.2024	Engineer:	R.M	Drawn:	Y.X.C
Scale @ A1:	AS SHOWN	Checked:	BBB	Sheets:	7
Reference No.	VIC240193	Drawing No.	C9000	Rev.	B

© This drawing is copyright to Intrax Consulting Engineers. No part of this drawing shall be used for any other purpose without the prior written consent of Intrax Consulting Engineers.



- NOTES:**
- PITS DEEPER THAN 0.9 METRE SHALL BE FITTED WITH STEP IRONS.
  - STEP IRONS SHALL BE LOCATED:
    - DIRECTLY BELOW THE OPENING IN THE COVER.
    - DESIRABLY ON A WALL WITHOUT OPENINGS.
    - DESIRABLY ON ONE OF THE LONG SIDES OF THE PIT.
  - STEEL FOR STEP IRONS SHALL BE STRUCTURAL GRADE 250 TO AS3679/1990 PART 1.
  - STEP IRONS SHALL BE HOT DIP GALVANIZED AFTER FABRICATION TO AS/NZS 4680.
  - STEP IRONS SHALL HAVE SHARP EDGES ROUNDED.

B	CONCEPT	20.08.24	R.M
A	PRELIMINARY	02.08.24	R.M
Rev.	Remark/Comment	Date:	Appr.

Client:  
MLC

Architect:  
NEOSCAPE PTY LIMITED



Project:  
MLC SCHOOL DEVELOPMENT  
10-14 LOFTS AVENUE, KEW

Drawing:  
CIVIL SERVICES  
DETAILS

THIS DRAWING HAS BEEN DOCUMENTED IN COLOR AND MUST BE PRINTED IN COLOR, OTHERWISE INFORMATION WILL BE LOST

**CONCEPT**  
NOT FOR CONSTRUCTION

Date:	JUL.2024	Engineer:	R.M	Drawn:	Y.X.C
Scale @ A1:	AS SHOWN	Checked:	BBB	Sheets:	7
Reference No.	VIC240193	Drawing No.	C9001	Rev.	B

© This drawing is copyright to Intrax Consulting Engineers. No part of this drawing shall be used for any other purpose without the prior written consent of Intrax Consulting Engineers.

## Rohan Medley

---

**From:** Adrian Liistro <Adrian.Liistro@boroondara.vic.gov.au>  
**Sent:** Monday, 19 August 2024 10:59 AM  
**To:** Rohan Medley  
**Subject:** Stormwater Drainage Requirements - 10-14 Lofts Avenue, Kew

Hi Rohan,

In response to your request for drainage/on-site detention requirements we advise that the following are to be incorporated into your drainage design for Council approval.

Address: 10-14 Lofts Avenue, Kew  
Development type: 2 Dwelling development

Total Site area (m2): 710 m2

Roof Area (m2): 247 m2

Paved Surfaces (m2): 247 m2

Landscape (m2): 216 m2

Site Coverage (m2): 69.57%

Permissible Site Discharge	<b>5.7</b>	litres per second
OSD Volume Required	<b>5.8</b>	Cubic Metres

For the design of the stormwater Onsite detention (OSD) system:

- The volume requirement may be achieved by utilising an underground pipe/other approved storage system. Combined RW harvesting/OSD systems are not acceptable. Specifically; above ground rainwater tanks may not be utilised for this purpose.
- A 'sharp edged steel plate orifice' to control the discharge is the preferred method to achieve while not exceeding the permissible site discharge rate under normal conditions.
- All surfaces are to be drained to/and controlled by an orifice control pit (SD999 Revision 'J' as attached) and the site stormwater outlet is to fully 'control' the site.
- The invert level of the final connection point is to be confirmed on site and noted on the plan as "invert level confirmed on site". Council standard drawing SD 999 is only a guidance. You have to design your own control pit and provide the detailing such as the exact horizontal distance from the base of the mesh to the outlet wall, 300mm wide x 50mm deep sump area, the exact angle length of the mesh etc. to an approximate scale and reference SD 999 for detailing.
- A tabulation of pipe & pit volumes demonstrating a final volume as achieving the minimum requirement as per above.
- Make sure to indicate the proposed trees in the drainage plans (as per the endorsed landscape plan).
- During rainfall events that exceed the design intensity/duration; provide a safe escape route for surcharge to minimise damage to the property or adjoining properties.

- Please provide a copy of this email with your subsequent design submission.

You can submit plans, calculations and payment via Council web site now. Please refer the link below.

<https://service.boroondara.vic.gov.au/get-approval-for-an-on-site-detention-osd-system/>

- If proposed any excavation within the property >1.2m height, Council can't allow to discharge the seepage /Ag/ basement water to laneway or kerb and channel directly or indirectly.  
(please refer Ground Water Disposal Factsheet for more details)

Do not hesitate to contact me if you have any further enquiries. For regular follow up and registration, please email all future correspondence to [boroondara@boroondara.vic.gov.au](mailto:boroondara@boroondara.vic.gov.au)

Regards,

**Adrian**  
Drainage Engineer  
Asset & Capital Planning | Places & Spaces

8 Inglesby Rd, Camberwell, 3124 Victoria  
(03) 9278 4444



The City of Boroondara acknowledges the Wurundjeri Woi-wurrung people as the Traditional Owners and original custodians of this land, and we pay our respects to their Elders past and present.

This email, including any attachments, may contain confidential and/or privileged information and is intended solely for the use of the named recipient(s). If you are not the intended recipient, any unauthorised review, use, disclosure, copying, or distribution is strictly prohibited. If you have received this email in error, please notify the sender immediately and delete this email and any attachments from your system. Please note that any views or opinions presented in this email are solely those of the author and do not necessarily represent those of the City of Boroondara. The recipient is responsible for checking this email for viruses. The City of Boroondara is not liable for any loss or damage suffered by viewing or opening the content of this email.

## Storage Calculation Sheet

Pipe Storage:

Diameter (mm)	Length (m)	Capacity (m <sup>3</sup> )
450	24.2	3.849
		0.000
		0.000
		0.000
		0.000
		0.000
		0.000
		0.000
		0.000
		0.000

Pit Storage:

	Length (mm)	Width (mm)	Depth (mm)	Capacity (m <sup>3</sup> )
Pit 2	900	900	670	0.543
Pit 3	900	900	630	0.510
Pit 4	900	900	590	0.478
Pit 5	900	900	520	0.421
				0.000
				0.000
				0.000

**Total Required Storage:** 5.8 m<sup>3</sup>

**Total Available Storage:** 5.80 m<sup>3</sup>

**Available Storage is Satisfactory**

## Orifice Size Calculation

$$A = \frac{Q}{C_D \sqrt{2g \times h}}$$

$$\begin{aligned} A &= \pi r^2 \text{ m}^2 \\ Q &= 5.7 \text{ l/s} \\ C_D &= 0.65 \\ g &= 9.8 \text{ m/s}^2 \\ h &= 0.67 \text{ m} \end{aligned}$$

$$\begin{aligned} A &= 0.002405 \\ D &= 0.055 \end{aligned}$$

Orifice size required 55mm diameter