Y2 ARCHITECTURE		ST PATRICK'S PS BALLARAT STAGE 1 PROJECT NO: 1730		Y2	2.7 MATERIALS & COLOUR SCHEDULE INTERIOR & EXTERIOR ISSUE : TOWN PLANNING TP1	ULE			
ITEM	CODE	DESIGN CODE / COLOUR	DISTRIBUTOR / MANUFACTURER	IMAGE	INDICATIVE LOCATION	FIRE GRP	REV		
BLINDS	BL1	INTERNAL ROLLER BLIND - MOTORIZED SUNSCREEN FABRIC EUROVISION METALLISED TRANSPARENT BACKING COLOUR: KIEV MECHANISM: MANUAL SS CHAIN 2400MM WIDE, 100% TREVIRA CS BRACKETS: BLACK PLASTIC CHAIN DRIVE: BLACK RAIL: NATURAL ANODISED	VERTILUX DEBRA MATHIAS M. 0438 888 407	KIEV	TENDER OPTION 3 REFER TO SPECIFICATION CLAUSE 15.36 FOR SCOPE & FURTHER DETAILS MULTIPURPOSE HALL ONLY EAST GLAZING: W2.01.2				
COLORBOND	COB1	COLORBOND COLOUR: SHALE GREY	BLUESCOPE STEEL		ROOF, FLASHING, CAPPINGS, EAVES GUTTERS, GABLE BACKLINING, PLANT INTERNAL WALLS				
	ZINC	COLORBOND ROOF COLOUR: ZINCALUME	BLUESCOPE STEEL	////////	ROOF AS CODED				

ADVERTISED PLAN

This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any convright

Y2 ARCHITECTURE		ST PATRICK'S PS BALLARAT STAGE 1 PROJECT NO: 1730		Y2	2.7 MATERIALS & COLOUR SCHEDULE INTERIOR & EXTERIOR ISSUE : TOWN PLANNING TP1		
ITEM	CODE	DESIGN CODE / COLOUR	DISTRIBUTOR / MANUFACTURER	IMAGE	INDICATIVE LOCATION	FIRE GRP	REV
COMPRESSED FIBRE CEMENT	CFC1	JAMES HARDIE - COMPRESSED CEMENT SHEET ARCHITECTURAL EXOTEC STANDARD SHEET SIZE: 900/1200 X 2400/2700/3000 X 9MM THICK FACTORY FINISH: SEALER FACTORY CUT EDGES TO REUIRED SIZES FIXING: COUNTERSINK SCREWS FOR PAINT, WITH EXPRESSED 6/9MM BLACK SHADOWLINE COLORBOND STRIPS BEHIND PAINTED ON SITE AS SPECIFIED	NIKITAS SMIRNIOS 0466 477 337 13 11 03 NIKITAS.SMIRNIOS @JAMESHARDIE.CO M.AU		EXTERNAL WALL LININGS & SOFFITS AS CODED	NON COMB	
	CFC2	CEMBRIT PATINA ORIGINAL - EXTERNAL COLOUR: P333 [TERRACOTTA] 8M THICK PANEL SIZE: 1250 X 3050/2500MM INTEGRALLY COLOURED CEMENT SHEET FIXING: 8MM EXPRESSED JOINS & MECHANICAL FIXING, MATCHING POWDERCOATED RIVETS AT 450/600MM CRS, BLACK TAPE & BACKING STRIPS REFER TO MANUFACTURERS INSTALLATION GUIDE FOR VENTILATED FACADE SYSTEMS LEAD TIME: 22 WEEKS WARRANTY: 10 YEARS DEEMED TO SATISFY EXTERNAL FIRE EN 13501-1: NON COMBUSTIBLE	TRUMARK GROUP TONY 0422 869 841 1300 005 052 t.mckay@trumarkg roup.com.au		SOFFITS AS CODED	NON COMB	
	CFC3	JAMES HARDIE - FIBRE CEMENT SHEET VERSILUX LINING, 9MM TO MATCH EXISTING SHEET SIZE: 1200 X 2400/3000/3600 X 9MM THICK FACTORY FINISH: SEALED FIXING: COUNTERSINK SCREWS FOR PAINT, WITH SQUARE EDGE BUTT JOINS TO MATCH EXISTING PAINTED ON SITE AS SPECIFIED	NIKITAS SMIRNIOS 0466 477 337 13 11 03 NIKITAS.SMIRNIOS @JAMESHARDIE.CO M.AU		SOFFITS AS CODED: TO MATCH EXISTING	NON COMB	
L					This copied document to be made available		
			PLAN 2/7	SED	for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any convright		



Y2 ARCHITECTURE		ST PATRICK'S PS BALLARAT STAGE 1 PROJECT NO: 1730	INTERIOR & EXTERIOR					
ITEM	CODE	DESIGN CODE / COLOUR	DISTRIBUTOR / MANUFACTURER	IMAGE	INDICATIVE LOCATION	FIRE GRP	REV	
CONCRETE PANEL PRE CAST	CP1	PRE CAST CONCRETE PANEL - FULL DEPTH COLOUR CONCRETE COLOUR SYSTEMS COLOUR: APOLLO GREY CEMENT, PRE CAST CONCRETE SPECS: CLASS 2-C CONCRETE STRENGTH: 40MPA TBC FINISH: GRAFFITI COATING TO FULL EXTENT: [P9] SUBJECT TO ON SITE SAMPLE APPROVAL	CCS	CCS Apollo				
GLAZING	GL1	VIRIDIAN OFLOAT SUPER TONES TOUGHENED SAFETY GLASS COLOUR: SUPERGREEN OR GREEN 10MM THICK TBC THICKNESS: 6MM SUBMIT SAMPLE FOR APPROVAL CONDUCT A THERMAL STRESS & FRACTURE RISK ASSESSMENT IN COMPLIANCE WITH AS1288-2006	OCEANIA GLASS 1800 810 403 JOHN STEF archsupport@ocea niaglass.com.au	SuperGreen	ACCENT GLAZING AS CODED SECTION J COMPLIANCE SHADING COEFF & U VALUE FROM ENGINEER			
	GL2	FIRE RATED FIXED GLAZING REFER SPECIFICATION						
GLAZING FILM	GF1	FILM: SX-324 FROSTED SPARKLE AS SHOWN ON ELEVATIONS 75MM CONTINUOUS HORIZONTRAL STRIP AS DOCUMENTED SHEET WIDTH: 1219/1524MM	WINDOW ENERGY SOLUTIONS PH 1800 049 747 info@windowenerg ysolutions.com.au ALICIA		PROTOTYPE SAMPLE TO BE SUBMITTED FOR APPROVAL PRIOR TO MANUFACTURE			
	GF6	SOLAR PERFORMANCE FILM FOR WEST & EAST FACING CLERESTORY GLAZING: SOLARGARD TRUEVUE OR AVERY DENNISON OPTITUNE, METALISED MIRRORED FILMS AS RECOMMENDED BY LOCAL CONTRACTOR SAMPLE TO BE APPROVED BY SCHOOL			AS CODED ON DRAWINGS			
					This copied document to be made av			
			3/7		its consideration and review as part of a planning process under Planning and Environment Act 19 The document must not be used for purpose which may breach any	the 987. • any		

convright



Y2 ARCHITECTURE		ST PATRICK'S PS BALLARAT STAGE 1 PROJECT NO: 1730		Y2	2.7 MATERIALS & COLOUR SCHEDULE Interior & Exterior ISSUE : TOWN PLANNING TP1		
ITEM	CODE	DESIGN CODE / COLOUR	DISTRIBUTOR / MANUFACTURER	IMAGE	INDICATIVE LOCATION	FIRE GRP	REV
HANDRAILS	HR1	MODDEX CODE: AR110 DOUBLE OFFSET HANDRAIL ON HOB - PRIMARY SCHOOLS FINISH: POWDERCOAT/PAINT [PC1] IN ACCORDANCE WITH MODDEX SPECIFICATIONS INSTALLATION: BY A MODDEX ACCREDITED INSTALLER DULUX DURATEC OVER SAND BLASTED HOT DIP GAL STANDARD MODDEX 5 YEAR WARRANTY	MODDEX 1800 663 339 info@moddex.com.a u		EXTERNAL		
	HR2	MODDEX CODE: AR120 DOUBLE OFFSET HANDRAIL/KERBRAIL-PRIMARY SCHOOLS FINISH: POWDERCOAT/PAINT [PC1] IN ACCORDANCE WITH MODDEX SPECIFICATIONS INSTALLATION: BY A MODDEX ACCREDITED INSTALLER DULUX DURATEC OVER SAND BLASTED HOT DIP GAL STANDARD MODDEX 5 YEAR WARRANTY	MODDEX RICK		EXTERNAL		
	HR3	MODDEX CODE: CB40 BALUSTRADE SINGLE OFFSET HANDRAIL FINISH: POWDERCOAT/PAINT [PC1] IN ACCORDANCE WITH MODDEX SPECIFICATIONS INSTALLATION: BY A MODDEX ACCREDITED INSTALLER DULUX DURATEC OVER SAND BLASTED HOT DIP GAL STANDARD MODDEX 5 YEAR WARRANTY	MODDEX	t all	EXTERNAL		
	HR4	MODDEX CODE: CB45 BALUSTRADE SINGLE OFFSET HANDRAIL & KERBRAIL FINISH: POWDERCOAT/PAINT [PC1] TBC	MODDEX		EXTERNAL		
is copied document for the sole purp its consideration	ose of ena	FABRICATE IN ACCORDANCE WITH MODDEX SPECIFICATIONS INSTALLATION: BY A MODDEX ACCREDITED INSTALLER DOVOX DOVATEC OVER SAND BLASTED HOT DIP GAL INTREDARD MODDEX 5 YEAR WARRANTY					
part of a planning part of a planning planning and Envir Planning and Envir The document must purpose which m	orocess un onment A not be use	nder the .ct 1987. ed for any	4/7	<u> </u>	I		ļ

convright

Y2 ARCHITECTURE		ST PATRICK'S PS BALLARAT STAGE 1 PROJECT NO: 1730	AGE 1 INTERIOR & EXTERIOR				
ITEM	CODE	DESIGN CODE / COLOUR	DISTRIBUTOR / MANUFACTURER	IMAGE	INDICATIVE LOCATION	FIRE GRP	REV
METAL CLADDING	MC1	LYSAGHT PROFILE: SPANDEK 0.48MM BMT EXPOSED FIXING COLOUR: [COB1] + [ZINC] AS CODED ON DWGS	LYSAGHT 1800 641 417 SALES 13 30 38		CLADDING/ROOFING AS CODED		
	MC2	LYSAGHT PROFILE: FLAT 0.48MM BMT EXPOSED FIXING COLOUR: [COB1] REFER TO SPECIFICATION			ROOFING/FLASHING AS CODED & DETAILED		
	MC3	2 OFF, INSTALLED END TO END DE-FENCE MESH PANEL 1150 X 1200MM POWDERCOATED BLACK	TSS TRAFFIC SAFETY SYSTEMS		ROOF BALL GUARD		
NOSING	NOS2	EXTERNAL CONCRETE CARPET NOSING TREDFIX DOMAIN SERIES PROFILE: DKR104 PROFILE COLOUR: NATURAL ANODISED ALUMINIUM INSERT: BLACK CARBORUNDUM INSERT SLIP CLASSIFICATION: P5 30% LUMINANCE CONTRAST TO PAV9 REQUIRED	CLASSIC ARCHITECTURAL GROUP 1300 244 377 JERRY MOB 0439 106 008		EXTERNAL STAIRS	SLIP: P5 WET	

ADVERTISED PLAN

This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any convright

Y2 ARCHITECTURE		ST PATRICK'S PS BALLARAT STAGE 1 PROJECT NO: 1730		Y2	2.7 MATERIALS & COLOUR SCHEDULE Interior & Exterior ISSUE : TOWN PLANNING TP1	.E	
ITEM	CODE	DESIGN CODE / COLOUR	DISTRIBUTOR / MANUFACTURER	IMAGE	INDICATIVE LOCATION	FIRE GRP	REV
PAVING	PAV1 PAV2	INTEGRALLY COLOURED CONCRETE CONCRETE COLOUR SYSTEMS: BLUE GUM 1 BAG PER M CUBED LIGHT BROOM TEXTURE CONCRETE SLAB RANDOM MULTIDIRECTIONAL PATTERN SLIP RATING: R11/P4 CLEAR SEALER TO FULL EXTENT CCS: STREETSCAPE WATER BASED, NATURAL PENETRATING SEALER RECYCLED RED BRICK PAVING HERRINGBONE PATTERN LIFT EXISTING RED BRICK PAVING, MIX RED BRICKS FROM DEMOLISHED SHED EVENLY WITH EXISTING BRICKS, RE LAY IN HERRINGBONE PATTERN AS DOCUMENTED LAY BRICKS OVER: 100MM THICK CONCRETE SLAB +	CONCRETE COLOUR SYSTEMS	CCS Blue Gum	EXTERIOR PAVING AS CODED	SLIP: R11/P4	
	CONC	100MM THICK CRUSHED ROCK NATURAL GREY CONCRETE LIGHT BROOM TEXTURE CONCRETE SLAB RANDOM MULTIDIRECTIONAL PATTERN SLIP RATING: R11/P4 CLEAR SEALER TO FULL EXTENT CCS: STREETSCAPE WATER BASED, NATURAL PENETRATING SEALER				SLIP: R11/P4	

ADVERTISED PLAN

This copied document to be made available for the sole purpose of enabling its consideration and review as part of a planning process under the Planning and Environment Act 1987. The document must not be used for any purpose which may breach any convright



Y2 ARCHITECTURE		ST PATRICK'S PS BALLARAT STAGE 1 PROJECT NO: 1730		Y2	2.7 MATERIALS & COLOUR SCHEDULE INTERIOR & EXTERIOR ISSUE : TOWN PLANNING TP1		
ITEM	CODE	DESIGN CODE / COLOUR	DISTRIBUTOR / MANUFACTURER	IMAGE	INDICATIVE LOCATION	FIRE GRP	REV
PAINT COLOURS	P4	DULUX TO MATCH COLORBOND SHALE GREY	DULUX		EXTERNAL PAINT & PVC DOWNPIPES AS CODED		
	P5	DULUX BLACK CAVIAR SN4H9	DULUX		NEW BOX FASCIAS AS CODED		
	EXP-W	EXISTING OFF WHITE WINDOW & DOOR FRAMES TO MATCH EXISTING WINDOW FRAMES			PAINT ALL EXISTING OFF WHITE WINDOW & DOOR FRAMES		
	EXP-G	EXSTING GREEN WINDOW FRAMES TO MATCH EXISTING GREEN FRAMES			PAINT ALL EXISTING GREEN WINDOW FRAMES		
POWDERCOAT	PC1	DULUX DURATEC ZEUS STOCK PRODUCT COLOUR: BLACK MATT 90Z9202M APPLIED BY A REGISTERED ALUMINIUM APPLICATOR OFFERING A 25 YEAR DURABILITY WARRANTY OFFERING A 15 YEAR COLOUR RETENTION WARRANTY	DULUX		EXTERNAL DOOR/WINDOW FRAMING		
SUNSCREEN MESH	SUN1	KAYNEMAILE - SUNSCREEN MESH CUSTOM COLOUR: JADE GREEN OPAQUE COLOUR LEAD TIME: 10 WEEKS WARRANTY: 10 YEARS	KAYNEMAILE		MULTI PURPOSE BLDG: EAST FAÇADE		
TACTILE INDICATORS	TAC1	COBBLETAC PORCELAIN TACTILE PAVING TYPE: HAZARD STUD COLOUR: BLACK, SLIP: R12 SIZE: 300 X 300 X 10MM + 5MM STUD INSTALLATION: SLAB SET DOWN NOM 20MM FINISHED FLUSH WITH CONCRETE PAVING NOTCHED TROWEL ADHESIVE GROUT: ARDEX FG8 MIDNIGHT 202	CTA PH 1300 282 282		EXTERNAL TACTILE INDICATORS, FLUSH FINISH WITH CONCRETE PAVING This copied document to be made availa for the sole purpose of enabling its consideration and review as		
		<u> </u>	7/7		part of a planning process under the Planning and Environment Act 1987 The document must not be used for a		1

purpose which may breach any